
MARKSMAN® 1600HSi

"The World's Most Trusted High Speed Can Wrap Machine"

CAN PACKAGING SYSTEM


Marksman 1600HSi machine now runs multiple diameter cans and larger pack sizes, including 10-pack and 12-pack.




INTERNATIONAL. INC.

Marksman® 1600 HSi Specifications

Machine Footprint




Standard Package Styles



Top/Bottom Corner Gusset

Optional Package Styles



Straight Wrap

Key Features

Top and Bottom Gussets

Cans are securely wrapped in top and bottom gusseted packages that require less paperboard than other multipack paperboard packaging.

High Speed Packaging

Unpitched product flow allow speeds up to 2,400 cans per minute.

Complete Guarding

Walk-in sliding doors
Complete interlock safety guarding

Quick and Simple Changeover

Changeovers are optimized with our no-tool adjustment technology.

PLC Control

Uses advanced software technology.

Machine Dimensions

14"1" long, 5'10" wide, 7'1" high (4.30m x 1.78m x 2.16m)

Machine Weight

Approximately 11,460 lbs. (5198kg)

Speed Range

Operates at speeds up to

	Line	Surge
2x2	400ppm	450ppm
2x3	350ppm	400ppm
2x4	250ppm	300ppm
2x5	200ppm	240ppm
2x6	166ppm	200ppm
1x pag	cks - Same pom	as 2x packs

Air Requirements

With Vacuum Pump: 80 PSI - 3 CFM (6 Bar - 5 m3/H) Standard With Pneumatic Vacuum Option: 80 PSI - 22 CFM (6 Bar - 16 m3/H)

Electrical

400/460 VAC, 24 Kw 3 Phase, 50/60 Hz

Lubrication

No oil or grease needed

Package Configurations

Standard 2x2, 2x3, 2x4 Optional 2x5, 2x6

Product Ranges

Standard - Fixed diameter, multiple heights Optional - Up to four different diameters*

Min Diameter	53mm
Max Diameter	66mm

Min Height 79mm Max Height 189mm





Graphic Packaging International, Inc. 1500 Riveredge Parkway Atlanta, GA 30328 Phone (770)240-7200 Fax (770)937-9107 www.graphicpkg.com

^{*} Subject to product and package configurations